

Technical data

		D7760	D7780
Weight	g/m ²	60	80
Thickness	mm	0,30*	0,40*
Roll length	m	100	100
Roll width	m	1,1	1,1
Resin uptake	kg/m ²	~400*	~550*
Binder		NO binder**	No binder**
Fibre		Polycralic	Polycralic
Elongation	%	100	100

* depending on process pressure

** mechanically bonded (needled veil)

Lantor Finishmat® D7760/80

- Excellent surface finish
- Reduction of process cycle time
- Gelcoat can be replaced by pigmented resin
- Easy to process
- Becomes translucent in resin
- High elongation

Applications of Lantor Finishmat® D7760/80

- Transportation (parts and panels of cars, trailers, trucks, RV's)
- Marine (hulls, decks and lids of boats and yachts)
- General closed mould applications

Lantor Finishmat® D77 grades provide an excellent surface finish for products made in closed mould processes



The finishing touch!

- Excellent surface finish
- Fibre print blocker
- Reduce process cycle time
- Cost efficient

The information contained in this document has been compiled in good faith by Lantor B.V., but nevertheless no representation or warranty is given as to the accuracy or completeness of the (technical) information provided herein. Please note, the data presented in this document are typical values only, and should not be used as specification or engineering data. Lantor B.V. can not be held liable for any damages arising from any (printing) errors or omissions in this information. Lantor B.V. reserves the right to make changes with respect to the information provided at any time without further notice.

For more information:

Lantor BV

Verlaat 22, P.O. Box 45
3900 AA Veenendaal

The Netherlands

Tel.: +31 (0)318 - 537 111

Fax.: +31 (0)318 - 537 420

E-mail: lantorbv@lantor.nl

Or visit our website: www.lantor.nl